

PSX 300

Power Steering Fluid Exchanger



BOSCH

Invented for life



Power steering fluid exchange service is now faster and easier with the PSX 300!

Power steering fluid exchanges are being recommended as routine maintenance by a growing number of OEM's. The PSX 300 performs this profitable service efficiently and accurately – increasing shop revenue and customer satisfaction!

The PSX 300 can perform a complete power steering fluid exchange in 5-15 minutes average! The clear dual process hose saves time by only having one wand to insert into the power steering reservoir. Simply insert the wand into the reservoir, power the unit up to extract the old fluid, then refill the reservoir with new fluid, and turn the steering wheel lock-to-lock until the waste fluid matches the color of the new fluid

Features



- 1 Simple to operate by toggling the new and old fluid switches
- 2 New and used power steering fluid containers
- 3 Clear dual process hose saves time and allows visual monitoring of the service
- 4 Rugged cart has small footprint, saving valuable shop floor space
- 5 Storage shelf
- 6 Four heavy duty swivel casters



Four locking swivel casters increase maneuverability



Clear dual-process hoses saves time. Valved ends prevent fluid spills



Technician friendly controls increase efficiency

Essential Features:

- ▶ High-capacity waste pump provides enhanced cold temperature fluid extraction
- ▶ Extremely fast process times from the two positive-displacement diaphragm pumps
- ▶ No priming required
- ▶ User-friendly operation
- ▶ Compatible with multiple power steering fluid types
- ▶ Available without cart as an add-on installation to the ATX 200

F00E900818 PSX 300 w/ cart

F00E900819 PSX 300 w/o cart for installation on ATX 200

Specifications			
Electrical	12 VDC – 4 Amp	New Fluid Tank Capacities	1 gal (3.79 liter) clear PVC
Dimensions	45" x 22" x 21" (113 cm x 55 cm x 53 cm) (H x W x D)	Used Fluid Tank Capacities	1 gal (3.79 liter) clear PVC
Shipping Weight	48 lbs (22 kg).	Process Time	5 to 15 minutes average
Operating Range	32° to 122°F (0° to 50°C)	Fluid Types	Multiple power steering fluid capability
New Fluid Pump	Diaphragm type, 1 gal (3.79 liter) per minute	Casters	360° swivel; locking
Used Fluid Pump	Diaphragm type, 1 gal (3.79 liter) per minute	Warranty	1 Year parts & labor
Hoses	3/8" (0.95 cm) clear PVC		